

HYVA

We move your world



HA 22



HA22 E1

kg	2000*	1610	930	630	410
m	1,00	1,23	2,15	3,16	4,12

HA22 E2

kg	1970*	1505	880	620	410
m	1,00	1,31	2,23	3,16	4,12

HA22 E3

kg	1770*	1285	755	530	410	290
m	1,00	1,38	2,31	3,23	4,16	5,11

*) Theoretical lifting capacity

CE	<input checked="" type="checkbox"/>
NO CE	<input checked="" type="checkbox"/>
MANUAL	<input checked="" type="checkbox"/>
RADIO	<input checked="" type="checkbox"/>

MODELS	LIFTING MOMENT	MAX VERTICAL REACH (HYDR)	SLEWING ANGLE	SLEWING TIME	MAX WORKING HEEL	WORKING PRESSURE	CRANE WEIGHT WITHOUT STABILIZERS	OIL TANK CAPACITY	OIL FLOW	DIMENSIONS
	tm	m	°	s/180°	°	bar	kg	l	l/min	mm B x h x S
HA22 E1	2,00	3,6	335	10	3	160	216	17,5	8	695x1521x430
HA22 E2	-	4,5	335	10	3	160	243	17,5	8	710x1521x430
HA22 E3	-	5,5	335	10	3	150	265	17,5	8	868x1521x430