

HYVA

We move your world



HV 47



Model	kg	4300*	2150*	1250	965	705		
HV47 E1	m	1,00	2,00	3,23	4,44	5,75		
Model	kg	4170*	2085*	1250	900	705	540	
HV47 E2	m	1,00	2,00	3,33	4,54	5,75	7,06	
Model	kg	4060*	2030*	1180	845	650	540	425
HV47 E3	m	1,00	2,00	3,43	4,64	5,85	7,06	8,37

*) Theoretical lifting capacity

CE	<input checked="" type="checkbox"/>
NO CE	<input checked="" type="checkbox"/>
MANUAL	<input checked="" type="checkbox"/>
RADIO	<input type="checkbox"/>

MODELS	LIFTING MOMENT	MAX VERTICAL REACH (HYDR)	SLEWING ANGLE	SLEWING TIME	MAX WORKING HEEL	WORKING PRESSURE	CRANE WEIGHT WITHOUT STABILIZERS	OIL TANK CAPACITY	OIL FLOW	DIMENSIONS
	tm	m	°	s/180°	°	bar	kg	l	l/min	mm B x h x S
HV47 E1	4,30	7,22	380	16	4	270	565	48	14	2155x1955x420
HV47 E2	-	8,51	380	16	4	270	615	48	14	2155x1955x420
HV47 E3	-	9,81	380	16	4	270	660	48	14	2155x1955x420