

HYVA

We move your world



HV 77



HV77 E1

kg	7550*	3775*	2195	1560	1140
m	1,00	2,00	3,43	4,79	6,23

HV77 E2

kg	7340*	3670*	2085	1470	1140	870
m	1,00	2,00	3,51	4,87	6,23	7,66

HV77 E3

kg	7130*	3565*	1990	1405	1080	870	665
m	1,00	2,00	3,58	4,94	6,30	7,66	9,05

*) Theoretical lifting capacity

CE	<input checked="" type="checkbox"/>
NO CE	<input checked="" type="checkbox"/>
MANUAL	<input checked="" type="checkbox"/>
RADIO	<input checked="" type="checkbox"/>

MODELS	LIFTING MOMENT	MAX VERTICAL REACH (HYDR)	SLEWING ANGLE	SLEWING TIME	MAX WORKING HEEL	WORKING PRESSURE	CRANE WEIGHT WITHOUT STABILIZERS	OIL TANK CAPACITY	OIL FLOW	DIMENSIONS
	tm	m	°	s/180°	°	bar	kg	l	l/min	
HV77 E1	7,55	7,81	380	16	4	255	770	48	16	2320x2030x565
HV77 E2	-	9,22	380	16	4	255	830	48	16	2320x2030x565
HV77 E3	-	10,64	380	16	4	255	890	48	16	2320x2030x565