

HYVA

We move your world



HB 60



Model	kg	1,00	2,45	3,78	5,34	7,00	8,64	10,30	11,90
HB60 E1	6580*	2680**	1740	1230	885	655			
HB60 E2	6410*	2615**	1650	1150	885	655	490		
HB60 E3	6160*	2515**	1555	1070	810	655	490	400	
HB60 E4	5970*	2435**	1475	995	745	590	495	400	

CE	<input checked="" type="checkbox"/>
NO CE	<input checked="" type="checkbox"/>
MANUAL	<input checked="" type="checkbox"/>
RADIO	<input checked="" type="checkbox"/>

*) Theoretical lifting capacity
 **) Fixed hook capacity

MODELS	LIFTING MOMENT	MAX VERTICAL REACH (HYDR)	SLEWING ANGLE	SLEWING TIME	MAX WORKING HEEL	WORKING PRESSURE	CRANE WEIGHT WITHOUT STABILIZERS	OIL TANK CAPACITY	OIL FLOW	DIMENSIONS
	tm	m	°	s/180°	°	bar	kg	l	l/min	mm B x h x S
HB60 E1	6,58	8,34	387	15	4	245	800	35	20	2240x1980x600
HB60 E2	-	9,81	387	15	4	245	870	35	20	2240x1980x600
HB60 E3	-	11,34	387	15	4	245	930	35	20	2240x1980x600
HB60 E4	-	12,90	387	15	4	245	980	35	20	2250x1980x600