

**HYVA**

**We move your world**



# HB 80



Model	kg	1,00	2,45	3,85	5,40	7,05	8,66	10,35	11,95
<b>HB80 E1</b>	7890*	3220**	2050	1445	1050	790			
<b>HB80 E2</b>	7690*	3140**	1965	1370	1050	790	600		
<b>HB80 E3</b>	7420*	3030**	1865	1290	975	790	600	470	
<b>HB80 E4</b>	7190*	2935**	1760	1200	900	715	600	470	

\*) Theoretical lifting capacity  
 \*\*) Fixed hook capacity

CE	<input checked="" type="checkbox"/>
NO CE	<input checked="" type="checkbox"/>
MANUAL	<input checked="" type="checkbox"/>
RADIO	<input checked="" type="checkbox"/>

MODELS	LIFTING MOMENT	MAX VERTICAL REACH (HYDR)	SLEWING ANGLE	SLEWING TIME	MAX WORKING HEEL	WORKING PRESSURE	CRANE WEIGHT WITHOUT STABILIZERS	OIL TANK CAPACITY	OIL FLOW	DIMENSIONS
	tm	m	°	s/180°	°	bar	kg	l	l/min	
HB80 E1	7,89	8,50	387	15	4	285	850	35	20	2310x1980x600
HB80 E2	-	10,20	387	15	4	285	930	35	20	2310x1980x600
HB80 E3	-	11,70	387	15	4	285	990	35	20	2310x1980x600
HB80 E4	-	13,30	387	15	4	285	1050	35	20	2310x1980x600