

**HYVA**

**We move your world**



# HB 90

**EES**  
**SDS**

**HB90 E1**

kg	8700*	4120*	3105**	2130	1510
m	1,00	2,00	2,68	4,08	5,76

**HB90 E2**

kg	8240*	3900*	2990**	2020	1415	1095	710	600
m	1,00	2,00	2,68	4,08	5,76	7,45	9,41	11,21

**HB90 E3**

kg	8010*	3780*	2900**	1920	1716	900	790	600	475
m	1,00	2,00	2,68	4,11	5,79	7,54	9,34	11,21	13,22

**HB90 E4**

kg	7840*	3680*	2840**	1850	1230	920	710	600	475
m	1,00	2,00	2,68	4,24	5,92	7,61	9,41	11,21	13,22

\*) Theoretical lifting capacity      \*) Max lifting capacity  
 \*\*) Fixed hook capacity

CE	<input checked="" type="checkbox"/>
NO CE	<input checked="" type="checkbox"/>
MANUAL	<input checked="" type="checkbox"/>
RADIO	<input checked="" type="checkbox"/>

MODELS	LIFTING MOMENT	MAX VERTICAL REACH (HYDR)	SLEWING ANGLE	SLEWING TIME	MAX WORKING HEEL	WORKING PRESSURE	CRANE WEIGHT WITHOUT STABILIZERS	OIL TANK CAPACITY	OIL FLOW	DIMENSIONS
	tm	m	°	s/180°	°	bar	kg	l	l/min	mm B x h x S
HB90 E1	8,7	9,1	425	12	4	310	1030	75	40	2305X2070X840
HB90 E2	-	10,7	425	12	4	310	1110	75	40	2305X2070X840
HB90 E3	-	12,6	425	12	4	310	1190	75	40	2305X2070X840
HB90 E4	-	14,4	425	12	4	310	1260	75	40	2305X2070X840