

**HYVA**

**We move your world**



# HB 130

**EES**  
**SDS**

**HB130 E1**

kg	12440	6000*	4540**	2740	1940
m	1,00	2,00	2,69	4,54	6,34

**HB130 E2**

kg	11850	5720*	4330**	2610	1810	1395	1010	755	560
m	1,00	2,00	2,69	4,54	6,34	8,14	10,36	12,34	14,39

**HB130 E3**

kg	11430	5520*	4180**	2475	1690	1280	1015	755	560	410
m	1,00	2,00	2,69	4,62	6,42	8,22	10,2	12,34	14,39	16,49

**HB130 E4**

kg	11090	5330*	4050**	2355	1585	1175	910	755	560	410
m	1,00	2,00	2,69	4,71	6,51	8,31	10,29	12,27	14,39	16,49

**HB130 E5**

kg	10730	5170*	3920**	2245	1490	1085	825	665	560	410
m	1,00	2,00	2,69	4,78	6,58	8,38	10,36	12,34	14,39	16,49

\*) Theoretical lifting capacity    \*) Max lifting capacity  
 \*\*) Fixed hook capacity

CE	<input checked="" type="checkbox"/>
NO CE	<input checked="" type="checkbox"/>
MANUAL	<input checked="" type="checkbox"/>
RADIO	<input checked="" type="checkbox"/>

MODELS	LIFTING MOMENT	MAX VERTICAL REACH (HYDR)	SLEWING ANGLE	SLEWING TIME	MAX WORKING HEEL	WORKING PRESSURE	CRANE WEIGHT WITHOUT STABILIZERS	OIL TANK CAPACITY	OIL FLOW	DIMENSIONS
	tm	m	°	s/180°	°	bar	kg	l	l/min	
HB130 E1	12,4	9,9	425	12	4	285	1335	130	60	2480x2295x825
HB130 E2	-	11,7	425	12	4	285	1445	130	60	2480x2295x825
HB130 E3	-	13,7	425	12	4	285	1570	130	60	2480x2295x825
HB130 E4	-	15,7	425	12	4	285	1660	130	60	2480x2295x825
HB130 E5	-	17,8	425	12	4	285	1745	130	60	2480x2295x895