

HYVA

We move your world



HB 230



EES Extra Extension Speed
SDS Smooth Descent System
LCS Lift Control System

MODELS	LIFTING MOMENT	MAX VERTICAL REACH (HYDR)	SLEWING ANGLE	SLEWING TIME	MAX WORKING HEEL	WORKING PRESSURE	CRANE WEIGHT WITHOUT STABILIZERS	OIL TANK CAPACITY	OIL FLOW	DIMENSIONS
	tm	m	°	s/180°	°	bar	kg	l	l/min	mm B x h x S
HB230 E1	20,7	9,9	387	17	4	315	1890	130	40	2480x2295x970
HB230 E2	-	11,8	387	17	4	315	2040	130	40	2480x2295x970
HB230 E3	-	13,8	387	17	4	315	2180	130	40	2480x2295x1000
HB230 E4	-	15,7	387	17	4	315	2310	130	40	2480x2295x1000
HB230 E5	-	17,8	387	17	4	315	2410	130	40	2480x2295x1000
HB230 E6	-	19,8	387	17	4	315	2510	130	40	2480x2295x1000
HB230 E5J2	-	23,3	387	17	4	315	2745	130	40	2480x2300x1120

HB 230

EES

SDS

LCS



HB230 E1

kg	20660*	9620**	4765	3370
m	1,00	2,10	4,26	6,13

HB230 E2

kg	19980*	9415**	4665	3260	2490
m	1,00	2,10	4,26	6,13	8,00

HB230 E3

kg	19300*	9140**	4530	3095	2355	1905	1470	1145	905
m	1,00	2,10	4,26	6,13	8,00	9,95	11,90	14,00	16,10

HB230 E4

kg	18870*	8935**	4430	2995	2225	1755	1470	1145	905	650
m	1,00	2,10	4,26	6,13	8,00	9,95	11,90	14,00	16,10	18,30

HB230 E5

kg	18420*	8720**	4235	2820	2075	1635	1330	1145	905	650
m	1,00	2,10	4,35	6,22	8,10	10,05	12,00	14,00	16,10	18,30

HB230 E6

kg	18030*	8525**	4080	2700	1970	1535	1230	1045	905	650
m	1,00	2,10	4,42	6,30	8,16	10,10	12,10	14,10	16,10	18,30

HB230 E5J2

kg									605	550	505	400
m									16,70	18,10	19,60	21,10

*) Theoretical lifting capacity

**) Fixed hook capacity

CE	<input type="checkbox"/>
NO CE	<input checked="" type="checkbox"/>
MANUAL	<input checked="" type="checkbox"/>
RADIO	<input checked="" type="checkbox"/>