

HYVA

We move your world



HB 240



EES Extra Extension Speed
SDS Smooth Descent System

MODELS	LIFTING MOMENT	MAX VERTICAL REACH (HYDR)	SLEWING ANGLE	SLEWING TIME	MAX WORKING HEEL	WORKING PRESSURE	CRANE WEIGHT WITHOUT STABILIZERS	OIL TANK CAPACITY	OIL FLOW	DIMENSIONS
	tm	m	°	s/180°	°	bar	kg	l	l/min	mm B x h x S
HB240 E2	22,7	11,9	415	12	4	320	2200	130	80	2520X2300X930
HB240 E3	-	13,9	415	12	4	320	2355	130	80	2520X2300X930
HB240 E4	-	16,0	415	12	4	320	2505	130	80	2520X2300X930
HB240 E5	-	18,2	415	12	4	320	2625	130	80	2520X2300X930

HB 240

EES

SDS



HB240 E2

kg	22700*	8000°	5280	3610	2750
m	1,00	2,75	4,30	6,20	8,10

HB240 E3

kg	21870*	8000°	5085	3425	2570	2035	1530	1170	770
m	1,00	2,64	4,30	6,20	8,10	10,13	12,25	14,46	16,59

HB240 E4

kg	21160*	8000°	4820	3215	2380	1860	1530	1170	915	735
m	1,00	2,55	4,39	6,29	8,19	10,22	12,25	14,46	16,59	18,70

HB240 E5

kg	21490*	8000°	4585	3035	2220	1710	1390	1170	915	735
m	1,00	2,46	4,47	6,37	8,27	10,30	12,33	14,46	16,59	18,70

CE	<input checked="" type="checkbox"/>
NO CE	<input checked="" type="checkbox"/>
MANUAL	<input checked="" type="checkbox"/>
RADIO	<input checked="" type="checkbox"/>

*) Theoretical lifting capacity °) Max lifting capacity
 **) Fixed hook capacity